



SL700 Secure Communications

HOMELAND SECURITY STRATEGIES GB LTD

Secure Communication for Land line phones to protect both Voice & Data Transfers

- Secure Voice Calls
- Secure E-mail Attachments
- Secure Voice Communications via PBX
- Secure Point to Point File Transfers (connected to computer)
- Secure Files in any Computer, Network or on the Internet
- All This In Self Contained Units!

Secure communications has been a dangerous game until now. Thanks to the Secure Line 700 the game is over. HSS' remarkable breakthrough in communications security, the Secure Line 700 is a High Grade Encryption product that trumps technology with better technology.

This encryption product combines the communication technology of HSS with the Harris corporation's Citadel™ CCX cryptographic chip. The result is a compact and portable security system that ensures your e-mail, voice, fax, and data communications are secure.

The Secure Line 700 connects to ordinary telephone lines, allowing easy encryption of voice communication between Secure Line 700 units. The secure line 700 provides a simple method of encrypting your computer files. Select encrypt and save files through the Secure line 700 insuring that you important information is kept confidential. The encrypted files can be stored in computers networks or on the internet.



The Secure Line 700 can protect important information contained in your systems as well as securing the communication of an e-mail attachment and point to point file transfers.

Connect any compatible cell phone through the RS 232 Jack to the Secure Line 700, insuring cryptographic communications of information between the 2 secure Line 700's. The secure line 700 allows secure simultaneous voice communication (SVD) and file transfer over ordinary telephone lines.

The Secure Line 700 - because confidentially isn't a luxury, it is a necessity.

| | |
|---|---|
| Encryption Algorithm: | Harris CITADEL™ CCX or Triple DES: one algorithm per unit |
| Cryptographic Traffic Encryption Key: | 3.4 x 1038 combinations (128-bit key length) |
| Minimum Communication Speed: | 3200bps throughput |
| Satellite/Cellular Telephone Interface: | DB9 Serial Connector |
| Terrestrial Telephone Interface: | RJ-8 |
| Computer Interface: | DB9 Serial Connector |
| Weight: | 9oz |
| Power Source: | 90 to 240 Volts A/C 50 to 60 Hz |
| Battery: | Lithium Ion, providing up to 4 hours of secure operation in the wireless mode. Secure operation is possible while charging. |
| Power Consumption: | 3.5 Watts |
| Dimensions: | 6" D x 4.38" W x 1.38" H |
| | (152mm D x 111mm W x 35mm H) |
| PC Software: | Compatible with Windows 98, Windows NT, Windows 2000, Windows XP Windows® and Outlook® are trademarks of Microsoft Corp. |